




RoHS







Height(高度) :

NO.1	
PART NO	H
D	
F	7.25

Material:

Button 按钮	PBT/LCP耐温280°C
Cover plate 盖板	铁 (镀银)
Shrapnel 弹片	不锈钢 (复银)
Base 基座	PBT/LCP耐温280°C
Pin 引脚	磷铜 (镀银)



Main technical specifications:

Rated load(額定負荷):	DC 12V 50mA			
Contact impedance(接触阻抗):	≤100mΩ MAX			
Insulation impedance(绝缘阻抗):	≥100MΩ MIN			
Welding resistance temperature (耐焊温度):	250±5 ° 5s			
OPERATING LIFE (电气寿命):	5000,000 cycles			
Usage temperature (使用温度):	-25 °C to 85 °C			
Operating humidity (使用湿度):	≤85% RH			
Trip(行程):	0.25 ± 0.05mm			
Operating force(操作力):	1	90 ± 30gf	2	130 ± 30gf
	3	180 ± 50gf	4	250 ± 50gf
	5	350 ± 50gf	6	

NO.2

public errand (公差) : ±0.2mm unit (单位) : mm

LCZY ELECTRONICS(SHEN ZHEN)CO.,LTD

COPYRIGHT RESERVED,PLEASE DO NOT COPY.

PART NAME		SWITCH		DRAWING		G.L CHEN		DWG.No.		LCZY	
PART NO.		K2-1850DT		CHECK		Z.LIU		REV.		A1	
	UNIT :	TOLERANCE OTHERWISE	UP TO 5 ABOVE 5 ~30 ABOVE 30 ANGLE	±0.2 ±0.3 ±0.5 ±3°	ANGLE 0°±3°	APPROVAL		DATE		K2-09-2019	
						SCALE		PAGE		1 OF 1	

K2-1850DT-□-□