




RoHS



PCB Layout(Pattern side)



Circuit Diagram

Height(高度) :

NO.1	
PART NO	H
D	4.0
F	

Material:

Button 按钮	硅胶 (蓝色)
Cover plate 盖板	硅胶 (蓝色)
Pin 引脚	磷铜 (镀银)

Main technical specifications:

Rated load(额定负荷):	DC 12V 50mA
Contact impedance(接触阻抗):	$\leq 100m\Omega$ MAX
Insulation impedance(绝缘阻抗):	$\geq 100M\Omega$ MIN
Welding resistance temperature(耐焊温度):	$250 \pm 5^\circ$ 5s
OPERATING LIFE (电气寿命):	2000,000 cycles
Usage temperature (使用温度):	-65 to 200
Operating humidity (使用湿度):	$\leq 85\%$ RH
Trip(行程):	1.0 ± 0.2 mm
Operating force(操作力):	1 200 $\pm$ 40gf
	2

LCZY ELECTRONICS(SHEN ZHEN)CO.,LTD

COPYRIGHT RESERVED,PLEASE DO NOT COPY.

public errand (公差) : ± 0.2 mm unit (单位) : mm

PART NAME		SWITCH			DRAWING	G.L CHEN	DWG.No.	LCZY
PART NO.		K2-8810SP			CHECK	Z.LIU	REV.	A1
	UNIT :	TOLERANCE OTHERWISE	UP TO 5	± 0.2	APPROVAL		DATE	K2-09-2019
			ABOVE 5 ~ 30	± 0.3				
	mm		ABOVE 30	± 0.5	SCALE	2:1	PAGE	1 OF 1
			ANGLE	$\pm 3^\circ$				

K2-8810SP-□-□